

EPDM Primer

Primer for Adhesion to Existing Synthetic Rubber Roofing



Commercial Product Data Sheet

Description

EPDM Primer is a low viscosity adhesive primer designed to adhere to EPDM rubber, TPO and Hypalon membrane to allow application of Sealoflex products.

Preparation

Remove all loose and foreign matter from the area to be treated and thoroughly clean surface of the membrane before application.

Application

Apply a single light coat of EPDM Primer to the prepared area by brush, roller or low pressure sprayer and allow to dry thoroughly before applying the Sealoflex System.

Cleaning

Clean tools and equipment with mineral spirits.

Coverage

250 sq. ft./gal. depending on porosity of substrate.

Important Note: Thoroughly stir the product before use. When using a mechanical mixer, do not over agitate. Over agitating will add air into the product, creating bubbles.

Precautions

Read the MSDS on EPDM Primer carefully before application. Avoid contact with eyes and skin. If eyes become contaminated flush with water for at least 15 minutes and seek medical attention. If ingested do not induce vomiting. Seek medical attention immediately. Use only in well ventilated areas and avoid inhaling vapors. Use NIOSH approved respirators. Avoid contact with sparks, static electricity, open flame, motors and heat as EPDM Primer is FLAMMABLE!

ALWAYS have a CO₂ Fire Extinguisher within immediate reach of the application area.



Pour EPDM Primer out of can onto substrate



Apply EPDM Primer with brush, roller or spray. Allow to dry before applying the Sealoflex System

WARNING!

DO NOT plunge, submerge, dip, etc. applicator tools (rollers, brushes, etc.) into EPDM Primer buckets due to static electricity buildup. Sparks/Fire may result. Always **pour** EPDM Primer from the container onto the substrate.

EPDM PRIMER IS FLAMMABLE!

Electrostatic charge may accumulate and create a hazardous condition when handling or applying EPDM Primer.

ALWAYS USE PROPER GROUNDING PROCEDURES.

ALWAYS HAVE A CO₂ FIRE EXTINGUISHER WITHIN IMMEDIATE REACH OF THE APPLICATION AREA.

EPDM Primer

Physical and Mechanical Properties

Property (as Manufactured)	Value
Color	<i>Yellow</i>
Shelf Life and Storage Conditions	12 months if stored between +40°F & 90°F. <i>Do Not allow To Freeze.</i>
Dry Time	1 hour at 77°F, 50% RH
Application Temperature	+32°F to 105°F (Ambient) and +32°F to 130°F (Surface)
Packaging	5 gallon metal pails

Ed. July 2016