

Sealobond Primer

Penetrating Primer



Commercial Product Data Sheet

Description

Sealobond Primer is a deep penetrating low viscosity clear primer intended for chalky surfaces or where surface adhesion presents difficulties.

Uses

Sealobond Primer is designed to penetrate and wet out chalky or oxidized surfaces introducing a tough acrylic resin into the substrate to bind and form a sound substrate to accept top coats of various types thus providing improved adhesion to the substrate. Typical applications are:

- Many painted surfaces
- Concrete, masonry, stucco
- Synthetic stucco
- Lightweight concrete (not cellular lightweight concrete)

Advantages

- Penetrates readily into the substrate
- Easy to apply
- Forms a sound substrate suitable for coating
- Dries quickly
- Alkali resistant

Coverage

250 sq. ft./gal., depending on substrate

Instructions for Use

Surface Preparation

All surfaces must be clean, dry and free from oil, grease or loosely adhering particles.

Application

- Apply by brush, roller or airless spray equipment.
- Allow to dry 24 hours.

It is recommended that all concrete be tested for moisture content prior to application of Sealoflex Products. Structural concrete moisture should be <8%. Cellular Lightweight concrete moisture should be <19%.

If there is any doubt as to the correct method of surface preparation, please contact the Sealoflex Technical Department for specific recommendations.

Cleaning

Wash tools and equipment immediately after use with water. Cured Sealobond Primer can be removed with mineral spirits.



Sealobond Primer goes on milky white - dries clear.

Sealobond Primer

Physical and Mechanical Properties

Property (as Manufactured)	Value
Color	Milky White; Dries Clear
Shelf Life and Storage Conditions	12 months if unopened & stored between 40°F & 90°F <i>Do Not Allow To Freeze</i>
Application Temperature	+45°F to 105°F (Ambient) and +40°F to 130°F (Surface)
Density	8.5 lb./gal.
Packaging	5 plastic pails